# Ultima Series<sup>™</sup> Cardiorespiratory Diagnostic Systems



## MODEL:

# Ultima<sup>™</sup> CardiO<sub>2</sub>® Gas Exchange Analysis System

The Ultima Series<sup>™</sup> cardiorespiratory diagnostic systems offer maximum flexibility to configure both pulmonary function testing (PFT) and gas exchange testing. The Ultima<sup>™</sup> CardiO<sub>2</sub><sup>®</sup> gas exchange analysis system pairs two superior technologies to product one singularly powerful solution. This system combines our leading gas exchange technology with the premier Mortara® ECG. The result is an all-in-one, easy-to-use "gold standard" metabolic stress testing system.

- Fast responding oxygen and carbon dioxide sensors acquire data on a discreet breath-bybreath basis, providing continuous analysis and display of data.
- Simplified testing and data interpretation.
- Optional wireless ECG and thermal printer.



## UNIQUE SYSTEM DESIGN

allows for maximum testing comfort for the technician and the patient unparalleled performance and reliability.

- Fully adjustable desktop allows for expansive personal workspace
- Room to room portability with gas
- BreezeSuite Scheduler allows for



## FLOW SENSORS FOR SIMPLICITY AND ACCURACY

- Eliminates warm-up or flow
- Simple snap-in setup contains
- Options to use with a filter



## **TEST SPECIFIC** QUICK CALIBRATION

allows for simplified gas calibration





The Ultima Series<sup>™</sup> cardiorespiratory diagnostic systems offer maximum flexibility to configure both pulmonary function testing (PFT) and gas exchange systems. Simply select the product that best meets your needs, or talk to your product sales representative for more info.

| resting capabilities  | PF       | PFX          | СРХ       | CARDIO <sub>2</sub> | ССМ      |
|---|----------|--------------|-----------|---------------------|----------|
| PULMONARY FUNCTION TESTS:   |          |              |           |                     |          |
| <ul> <li>Spirometry (FVC, SVC, MVV)</li> </ul>                        | <b>~</b> | <b>~</b>     | <b>~</b>  | ✓                   | ✓        |
| <ul> <li>Respiratory mechanics (MIP/MEP)</li> </ul>                   | <b>~</b> | <b>~</b>     |           | Ο                   |          |
| <ul> <li>Diffusing capacity</li> </ul>                                | <b>~</b> | <b>V</b>     |           | Ο                   |          |
| <ul> <li>Nitrogen washout</li> </ul>                                  | <b>~</b> | $\checkmark$ |           | Ο                   |          |
| <ul> <li>Single breath N<sub>e</sub></li> </ul>                       | <b>~</b> | <b>~</b>     |           | Ο                   |          |
| <ul> <li>Arterial blood gases (ABG manual entry)</li> </ul>           | <b>~</b> | <b>~</b>     | <b>V</b>  | <b>~</b>            | ✓        |
| ECG/HEART RATE CONFIGURATIONS:<br>• Integrated 12-lead ECG            |          | 0            |           | V                   |          |
| GAS EXCHANGE TESTS:   |          |              |           |                     |          |
| <ul> <li>Direct fick cardiac output</li> </ul>                        |          | <b>~</b>     | <b>v</b>  | <b>~</b>            | <b>~</b> |
| <ul> <li>Indirect fick cardiac output (NICO)</li> </ul>               |          | Ο            | 0         | Ο                   | 0        |
| <ul> <li>Exercise capacity (O, and CO,)</li> </ul>                    |          | <b>~</b>     | ✓         | <b>~</b>            | Ο        |
| • Nutrition assessment: REE/RMR (O <sub>2</sub> and CO <sub>2</sub> ) |          | 0            | 0         | Ο                   | <b>~</b> |
|   |          |              | 🗸 standar | rd O optional       |          |

## SPECIFICATIONS

#### ULTIMA SYSTEM

- Workspace: W x D: 24 x 21 in (70 x 53.3 cm)
- Base: W x D: 25 x 31 (63.5 x 78.7 cm)
- Height: 49 in (124.5 cm)

#### PREVENT® FLOW SENSOR

- Bidirectional Pitot tube flow sensor
- Range: ±18 L/s
- Accuracy: ±3% or 50 mL, whichever is greater
- Resistance: <1.5 cm H<sub>2</sub>0 @ 14 L/s
- Dead space: 39 mL

### DIRECTCONNECT™ METABOLIC FLOW SENSOR

- Bidirectional Pitot tube flow sensor
- Patent number: 5,038,773
- Accuracy: ±3% or 10 mL, whichever is greater
- Resolution: 2.4 mL/s
- Range: 0–40 L/min
- Application range: 100-2000 mL
- Tidal volume range: 100-2000 mL

#### POWER REQUIREMENTS

• 100-240 V/50-60 Hz

### O<sub>2</sub> ANALYSIS

- Type: Galvanic
- Range: 0-100%
- Response: (10-90%) <180 ms
- Accuracy: ±1%

#### CO, ANALYSIS

- Type: Non-dispersive infrared (NDIR)
- Range: 0-15%
- Response: (10-90%) <180 ms
- Accuracy: ±0.1% (0-10% CO<sub>2</sub>)

## GAS SAMPLE

· Proprietary gas-drying sample circuit

## GAS REQUIREMENTS

#### ULTIMA CARDIO,

- Calibration gas: 5% CO<sub>2</sub>, 12% O<sub>2</sub>, bal N<sub>2</sub> (5-7 psi)
- Reference gas (recommended): 21% O<sub>2</sub>, bal N<sub>2</sub> (5-7 psi)

( F 0086

© 2019 MGC Diagnostics Corporation or one of its affiliates. All rights reserved. All specifications subject to change without notice. Products may vary from those illustrated. MGC Diagnostics and its affiliates are equal opportunity/affirmative action employers committed to cultural diversity in the workforce.

